Mectronic Ltd 13.10.2011

Do It Yourself:

Audi A4 and A6 Multitronic (01J) CVT-transmission ATF oil fill tool, will replace the VAS5162 tool



All needed parts bought mainly from Biltema, except the drain plug which is original VW/Audi part, all parts will cost about 25 €.

mectronic_diy_multitronic_oil_fill_tool.pdf www.mectronic.fi

Mectronic Ltd 13.10.2011

Part list (number of Biltema in parentheses) :

- 1 pc transparent PCV hove (oil resistant), inside diameter 12 mm (15-316), you need 1,8 m from 5 m length of hose
- 1 pc 3/8" lead-in (25-4341)
- 1 pc 3/8" ball valve (86-682)
- 1 pc 3/8" tailpiece, female (17-252)
- 1 pc quick coupler 12 mm, (17-248)
- 1 pc coupling ¹/₄" male thread (17-246)
- 2 pcs 11-13 mm hose clamp (61-847)


In addition, you will need:

- adapter (thread 22 x 1,5 mm) to drain plug thread. You can do it by buying a new and original inspection plug
- O-ring, about . 21 mm inside diameter, thickness 3 mm (comes to the adapter)
- plastic cap from 1 litre ATF oil bottle
- some sealant for threads



Notice! Quick coupler and ball valve is not necessary, but the removal of the hose adapter is more convenient when you remove the hose from adapter or when you change the bottle. Also ATF oil bottle cap can be replaced by a funnel, but using a funnel it means long time of flow for oil.

Mectronic Ltd 13.10.2011



mectronic_diy_multitronic_oil_fill_tool.pdf www.mectronic.fi Mectronic Ltd 13.10.2011

Notice!

This Multitronic transmission oil fill tool is almost identical with the <u>DSG oil fill tool</u>, only differences are the threads of the adapters and the size of the O-rings:

Difference of the oil fill adapters:

